

CK Series CK 146

144 l/m
38.1 USGPM

max 60 BAR
870 P.S.I.

APPLICAZIONI - APPLICATIONS



ATOMIZZATORI
ATOMIZERS





CLEANING
CLEANING

SPECIAL TRADEMARK

EL EASYtube™

Is INTELLiseal™

Sc SMARTcase™



CARATTERISTICHE TECNICHE SPECIFICATIONS	550 g/min. 550 R.P.M.	
Potenza - Power	16,6 KW	22.2 HP
Peso - Weight	39 Kg	85.8 lb
IN	2x40 mm	1"9/16 in
Pressione Min - Min Pressure	-0,15 BAR	- 2,17 P.S.I.
	-0,3 BAR (servizio discontinuo)	-0,435 P.S.I. (discontinuous service)
Pressione Max - Max Pressure	1 BAR	14.5 P.S.I.
OUT	G. 3/4	
Max. Temperatura - Max. Temperature	60 °C	140 °F
Tipo olio - Oil type	SAE 30	
Capacità olio - Oil capacity	2,8 lt	0.74 U.S.G.

TABELLA RENDIMENTI PERFORMANCE CHART								
g/min R.P.M.	400		450		500		550	
BAR P.S.I.	L/min USGPM	KW HP	L/min USGPM	KW HP	L/min USGPM	KW HP	L/min USGPM	KW HP
2 29	103,1 27,2	0,4 0,5	113,4 30,0	0,4 0,6	123,7 32,7	0,5 0,6	144,3 38,1	0,6 0,8
20 290	102,1 27,0	4,0 5,4	112,4 29,7	4,4 5,9	122,6 32,4	4,8 6,4	143,0 37,8	5,6 7,5
40 580	101,4 26,8	8,0 10,6	111,6 29,5	8,8 11,7	121,7 32,2	9,6 12,8	142,0 37,5	11,2 14,9
60 870	100,7 26,6	11,9 15,9	110,8 29,3	13,1 17,4	120,9 31,9	14,2 19,0	141,0 37,3	16,6 22,2

Versioni Versions

76.7310.97.3 - P

76.7311.97.3 - PP



Anteriore/Front

Posteriore/Rear

Anteriore/Front